



OPPBOGA



GENERAL

Oppboga Prominent is a twin-sided, fully coated board aimed for printing in offset and silk screen. The excellent printability and converting properties makes Prominent most suitable for graphical applications. Prominent is easy to work with when cutting, die cutting, punching, creasing and drilling.

APPLICATIONS

Oppboga Prominent is recommended for exclusive packaging, signs, folders, greeting cards, calendars, data sheets etc.

Substance gsm	Thickness µm	Bending stiffness Resonance mNm	
		MD	CD
370	490	55	29
400	620	90	50
450	680	125	65
500	800	190	105

Property	Target	Tolerance
Substance, gsm ISO 536	As specified	±5%
Thickness, µm ISO 534	As specified	±5%
Bending stiffness ISO 5629	As specified	-15%
Scott Bond, J/m ² TAPPI 569	120	Min 100
Moisture % ISO 287	Depending on substance	
Cobb 60, gsm ISO 535	30	Max 60
CIE Whiteness D65/10° ISO 11475	120	
Brightness, ISO C/2° ISO 2470	90	Min 87
Gloss 75°, % ISO 8254-1	40	
Surface smoothness, PPS, µm ISO 8791-4	1,3	Max 2,0

All properties according to Oppboga Mills measurements.

Test climate 23° C/50% (According to ISO 187)

Tolerances based upon 95% confidence limits, apply pallet average.

Date: 2010-11-25

Bernt Johansson

R & D & Quality Manager