



OPPBOGA



OPPBOGA

Passepartout

GENERAL

Oppboga Passepartout is a mounting board consisting of wood free, acid free paper buffered with calcium carbonate. The board is resistant to ageing in accordance with ISO 9706. Our Passepartout is available in the colours White, Extra White and Ivory. (The White Passepartout contains no optical brightening.)

APPLICATIONS

Oppboga Passepartout is recommended for mounting of graphical sheets, photos, drawings and stamp albums. Passepartout is used to avoid that the glass is in direct contact with the piece of art and has also an esthetical function. Passepartout can also be used as isolation to protect from the picture backing, if the backing board is not acid free.

Substance gsm	Thickness µm	Bending stiffness Resonance mNm	
		MD	CD
500	640	105	50
900	1150	670	330
1200	1475	1275	640

∞ Values can not be measured

Property	Target	Tolerance
Substance, gsm ISO 536	As specified	±10%
Thickness, µm ISO 534	As specified	±10%
Bending stiffness ISO 5629	As specified	-20%
pH	7,5 - 10	
Scott Bond, J/m ² TAPPI 569	120	Min. 100

All properties according to Oppboga Mills measurements.

Test climate 23^o C/50% (According to ISO 187)

Tolerances based upon 95% confidence limits, apply pallet average.

Date: 2007-03-20

Bernt Johansson
R & D & Quality Manager