

Oppboga Excellent™ Kraft

Virgin fibre board, brown paper on both sides

SUB-STANCE	THICKNESS		BENDING RESISTANCE L&W 15° mN		BENDING MOMENT Taber 15° mNm	
	g/m ²	µm pt	MD	CD	MD	CD
875	1500	59	*	*	*	*
1070	2000	79	*	*	*	*
1320	2500	99	*	*	*	*
1575	3000	118	*	*	*	*

*values cannot be measured



The natural choice for indoor advertising.

APPLICATIONS

Indoor Sign & Display

PRINTING

Offset printing • screen printing • large format digital printing

CONVERSION

Embossing • foil and film lamination • varnishing • die cutting • creasing • perforating • cutting and scoring

ADDITIONAL INFORMATION

www.oppboga.com

Tolerances / Testing Standards

Grammage (DIN ISO 536)	±10%
Thickness (DIN ISO 534)	±10%
Bending stiffness (ISO 5629)	±20%
Brightness C/2° (ISO 2470)	
Surface smoothness Bendtsen (ISO 8791-2)	

Printing Surface Properties

ISO Brightness	
CIE Whiteness D65/10° (ISO 11475)	
Surface smoothness (Bendtsen)	1500 ml/min
Gloss 75° (ISO 8254-1)	